Allegro Blowers

AC Axial Blower

With the highest output available from an 8" axial blower, this compact unit offers light weight and high output from an AC electric motor. It is designed with tough steel construction, a durable grill, convenient carrying handle and rubber feet. Its small profile means easy storage. Certified to CSA STD C22.2 No 113. Air delivery certified CEESI.

Free Air	One 90° Bend	Two 90° Bends
1275	661	582
19 lbs.	1/3 hp	3A / 115V

Part No.
9513

DC Axial Blower

Perfect for locations where electricity is not available, this 8" DC Axial Blower may be operated off a truck battery. It features a 12 volt DC electric motor with thermal protector, single speed performance. Extremely lightweight and portable, it includes a 15' cord with alligator clips.

Free Air	One 90° Bend	Two 90° Bends
1150	595	530
18 lbs.	1/4 hp	13A / 12V

Part No.
9506

Allegro Blowers

AC Axial Blower w/Canister-15 & 25

Engineered for convenience, this 8" axial blower is an all-in-one ventilation system. The design allows ducting to collapse into a built-in canister for easy storage. The unit can also be stored vertically to use a minimum amount of space. Includes blower, built-in storage canister and 15 or 25 feet of ducting. Certified to CSA STD C22.2 No 113. Air delivery certified CEESI.

Free Air	One 90° Bend	Two 90° Bends
1275	661	582

1/3 hp 3.3A/115V

Part No. 9514 15 ft. of ducting w/canister, 32lbs

Part No. 9514-25 25 ft. of ducting w/canister, 46lbs

Allegro Blowers

DC Axial Blower w/Canister-15 & 25

This complete, all-in-one ventilation system includes an 8" axial blower powered by a 12 volt DC motor, 15 or 25 feet of ducting and a built in storage canister. The handle and feet make this light weight system very portable and easy to store.

Free Air	One 90° Bend	Two 90° Bends
1150	595	530
	1/4 hp	13A / 12V

Part No. 9506-01 15 ft. of ducting w/canister, 31 lbs.

Part No. 9506-25 25 ft. of ducting w/canister, 37 lbs.

Allegro Blowers

AC Axial Explosion Proof Blower

Electric, explosion-proof motor is UL/CSA listed. Single-phase motor includes NEMA rated 115V plug for use with explosion-proof socket (included). It offers tough steel construction and meets Class I, Divisions I and II, Groups C and D and Class II, Divisions I and II, Groups E, F and G Hazardous Location Requirements. Warning: Explosion-proof Blowers must be used with statically conductive ducting.

Free Air	One 90° Bend	Two 90° Bends
890	825	770
20 lbs.	1/3 hp	3.3A / 115V

Part No. 9513-05	Blower only, 20 lbs.
Part No. 9514-05	15 ft. of ducting w/canister, 49 lbs.
Part No. 9514-06	25 ft. of ducting w/canister, 57 lbs.

Allegro Blowers

Axial Blower Ventilation Systems

Allegro introduces easy to order, easy to use Complete Ventilation Systems including all the most-asked-for equipment you need for your confined space site. The systems include a choice of Allegro's most popular blowers, six feet and fifteen feet of ducting with a storage bag, a Saddle Vent®, a 90° Elbow, and a Universal Mount. The Axial Blower Systems offer lightweight portability with the highest output available from axial-style blowers. See individual blower descriptions for CFM, weight and other specifications. Saddle Vent® is a registered trademark of Air Systems International, Inc.; the Saddle Vent® device is protected by U.S. Patent Nos 4,794,956, 4,982,653, and foreign patents.

Part No. 9520-06	DC Axial Blower System
Part No. 9520-14	AC Axial Blower System

Allegro Blowers

8 Inch Plastic AC COM-PAX-IAL Blower

Engineered with flexibility and job demands in mind, every feature of this super-quiet, high-output Com-PAX-ial Blower is designed for effectiveness and optimal air-flow performance. Compact blower and canister are made of durable, lightweight corrosion-, UV- and chemical-resistant polyethylene material. Sturdy, easy-grip handles molded directly into the blower and canister housing makes for convenient, reliable transport. This versatile unit offers the choice of 15’ or 25’ ducting, with the newly designed quick-connect clipping system allowing workers to attach canister, tools-free, to input side for powerful extraction or output side for ventilation. Ducting stores conveniently within canister. Choose complete blower and canister unit with 15’ or 25’ ducting, or blower only.

Free Air	One 90° Bend	Two 90° Bends
960 CFM	720 CFM	650CFM

Part No. 9533	8" Plastic AC COM-PAX-IAL Blower without canister, 17 lbs.
Part No. 9533-15	8" Plastic AC COM-PAX-IAL Blower with canister and 15
Part No. 9533-25	8" Plastic AC COM-PAX-IAL Blower with canister and 25

Allegro Blowers

AC COM-PAX-IAL Blower

Weighing 13% less than our 9513. This blower features a venturi inlet to increase CFM . Designed with tough steel construction, rubber feet, handle and a durable grill. Complete with AC electric motor. Blower sold separately or with quick-connect 15' or 25' ducting canister.

Free Air	One 90° Bend	Two 90° Bends
778	645	496
17 lbs	1/3 hp	3A/115V

Part No.
9534

DC COM-PAX-IAL Blower

The COM-PAX-IAL blower can run off a truck battery when you're on the road. 12 volt DC electric motor with single speed performance. Lightweight and easy to store. Features a 15' cord with alligator clips, durable grill, and tough steel construction. Comes with handle. Built to last. Blower sold separately or with quick-connect 15' or 25' ducting canister.

Free Air	One 90° Bend	Two 90° Bends
796	667	480
16 lbs.	1/4hp	13A/112V

Part No.
9537

Allegro Blowers

AC Com-PAX-ial Blower With Canister-15 & 25

This lightweight and compact Com-pax-ial blower can be an all-in-one ventilation system sold with quick-connect 15' or 25' ducting canister which attaches quickly without tools with Cam-lock latches.

Free Air	One 90° Bend	Two 90° Bends
778	645	496
	1/2 hp	3A/115V

Part No. 9534-15	AC Com-PAX-ial Blower w/15' Canister Assembly, 34lbs
Part No. 9534-15C	15' Canister conversion kit (use with 9534 & 9537)
Part No. 9534-25	AC Com-PAX-ial Blower w/25' Canister Assembly, 37lbs
Part No. 9534-25C	25' Canister conversion kit (use with 9534 & 9537)

Allegro Blowers

DC Com-PAX-ial Blower With Canister-15 & 25

All the same features of the AC model with CFM rate of 796 Free air. Blower with quick-connect 15' or 25' ducting canister. This attaches quickly without tools with Cam-lock latches. Both Blower and Canister come with handles.

Free Air	One 90° Bend	Two 90° Bends
796	667	480
	1/4 hp	13A/12V

Part No. 9537-15 DC Com-PAX-ial Blower w/15, 31 lbs.

Part No. 9537-25 DC Com-PAX-ial Blower w/15, 36 lbs.

12 Inch Standard Axial Blower

This unit can be used for both delivering fresh air or extracting contaminated air. Tough steel construction with handle and weighing only 27 lbs. makes this blower easy to transport. Add 12" standard ducting for greater flexibility. High RPM motor.

Free Air	One 90° Bend	Two 90° Bends
1763	1401	1227
27 lbs.	1/3 hp	3A/115V

Part No. 9509

Allegro Blowers

Standard Blower

Excellent for most ventilating needs, especially confined space. Designed with tough polyethylene housing, metal safeguards and a steel fan for durability. Two 8" ports offer positive ventilation or fume extraction, and the metal base with feet offers greater stability. The electric motor is cage-enclosed for protection. Comes with an on/off switch and built-in carry handle for increased portability. Works great with generators. Air delivery certified CEESI.

Free Air	One 90° Bend	Two 90° Bends
1066	839	745
38 lbs.	1/3 hp	6A /115V/.25KW

Part No.
9504

High Output Centrifugal Blower

For environments that require faster purge time or larger confined spaces, this High Output Blower offers the same features as the Standard Blower, with a cage-enclosed 3/4 hp motor for higher CFM output. Tough polyethylene housing offers lightweight durability, and the metal safeguards and steel fan offer greater safety.

Free Air	One 90° Bend	Two 90° Bends
1570	1100	900
45 lbs.	3/4 hp	12A /115V/230V

Part No.
9504-50

Allegro Blowers

Economy Lightweight Blower

An economy version of the Standard Blower, this lightweight blower comes in at only 41 lbs. It has a tough metal base and durable polyethylene housing, and works great with generators.

Free Air	One 90° Bend	Two 90° Bends
1066	839	745
41 lbs.	1/3 hp	6A /115V/.25KV

Part No.
9512

Heavy Duty Blower

High performance and durability are built into this Heavy Duty Blower. Its large 1 1/2 hp motor and 8" ports deliver high CFM allowing workers to draw out or push air in. It is designed with a large metal base with locking wheel casters and three carry handles for easy maneuverability. The electric motor is totally enclosed and the high impact polyethylene housing offers greater durability.

Free Air	One 90° Bend	Two 90° Bends
1700	1200	960
87 lbs.	1 1/2 hp	16A /115/230V

Part No.
9502

Allegro Blowers

Heavy Duty Explosion-Proof Blower

Electric, explosion-proof motor is UL/CSA listed. Single-phase motor includes Hazardous Location NEMA rated 115V plug for use with explosion-proof socket (included). ABS housing provides non-sparking safety. Meets Class I, Divisions I and II, Group D and Class II, Divisions I and II, Groups F and G Hazardous Location Requirements. Warning: Explosion-Proof Blowers must be used with statically conductive ducting.

Free Air	One 90° Bend	Two 90° Bends
1570	1100	900
76 lbs.	3/4 hp	11A /115/230V

Part No.
9503

Allegro Blowers

Gas Blower

Perfect for remote locations where electricity is unavailable, this gasoline-powered, 3 1/2 hp blower offers high flow rates. The 8" ports and steel guards provide safety and the polyethylene housing with built-in handle offers durability and convenience. It is designed with a sturdy metal base that minimize blower rocking and offers greater stability. Two quarts of gasoline will power 2-3 hours of running time. Blower includes 10 foot metal exhaust hose extension.

Free Air	One 90° Bend	Two 90° Bends
2000-3000	1500-2500	1350-2350
54 lbs.	3 1/2 hp Briggs and Stratton (four stroke)	
Part No. 9505		

Gas Blower / Honda

Same output and weight as the 9505. Offers greater durability with a Honda engine

Part No. 9505-50	4hp Honda (Four Stroke)

Allegro Blowers

Two Speed Blower

This blower offers greater flexibility by allowing workers to use high speed in some applications such as purging an area, and the lower speed in other sites such as very dusty environments. The 8" ports allow for positive or negative ventilation and the steel box mounted electric motor and tough polyethylene housing are designed for durability. Comes complete with in-line GFI and steel base for safety.

LOW SPEED			HIGH SPEED		
Free Air	One 90° Bend	Two 90° Bends	Free Air	One 90° Bend	Two 90° Bends
760	500	360	1850	1050	800
		4A /115V	64 lbs.	3/4 hp	10A /115V

Part No.
9507

Allegro Blowers

Air-Driven Blower

Ideal for areas where a compressor is readily available, this air-driven model requires 30 CFM at 40 psi. It uses an aluminum fan for explosion-proof requirements and includes a steel base, polyethylene housing, 2-stage filter, regulator, and lubricator. If used in hazardous environments, use statically conductive ducting.

Free Air	One 90° Bend	Two 90° Bends
1800	1350	900

43 lbs.

Part No.
9508

Allegro Blowers

Centrifugal Blower Systems

Allegro's Complete Ventilation Systems include all the most-asked-for equipment for your confined space site. The systems include a choice of Allegro's most popular blowers, six feet and fifteen feet of ducting with a storage bag, a Saddle Vent®, a 90° Elbow, and a Universal Mount. The Centrifugal Blower Systems offer lightweight portability with the highest output available. See individual blower descriptions for CFM, weight and other specifications.

Saddle Vent® is a registered trademark of Air Systems International, Inc.; the Saddle Vent® device is protected by U.S. Patent Nos. 4,794,956, 4,982,653, and foreign patents.

Part No. 9520-12	Economy Blower System
Part No. 9520-04	Standard Blower Systemn
Part No. 9520-50	High Output Blower System
Part No. 9520-05	Gas Blower System
Part No. 9520-08	Air Driven Blower System